

ALL PRODUCTS 2



BTALI INTERNATIONAL is an Indian based company Established In The Year 2001 .It is an ISO 9001:2015 Certified Company And Also Crisel Verified.

We Are Importing All Kinds Of Machinery & Pumps Mainly Air Compressors, High Pressure Washer, Submersible Pump, Pump Control Etc.

We have a team of Highly Qualified Employees & Skilled Engineers Which Work together to build a long relationship with Our Customers by offering them wide range of quality products.

Today We Are Privileged To Connect With More Than 200 Dealers Around India Through Our Best Products.





3 7 4 4 6 8 9 1

PRESSURE TANK BT 24 LVPT

VOLTAGE / FREQUENCY 220V/50HZ

Specifications

CONNECTOR
MEMBRANE
MAX PRESSURE
PRE-CHARGE PRESSURE
WORKING TEMPRATURE

1" STAINLESS STEEL INLET THREAD FIXED BUTYL RUBBER MEMBRANE EXPANSION TYPE 10 BAR/ 150 PSI 1.5 BAR 20 DEGREE C/+99 DEGREE C

FEATURES

NO MAINTENANCE LEAK FREE, ORING SEALED, AIR VALVE CAP COMPREHENSIVE TESTING SINGLE DIAPHARM DESIGN PATENTED STAINLESS STEEL WATER CONNECTION (3MM THICKNESS) FIXED MEMBRANE BUTYL DIAPHARM











ISO 9001:2015



BTALI®

PRESSURE TANK BT 60 LVPT

VOLTAGE / FREQUENCY 220V/50HZ

Specifications

CONNECTOR 1" STAINLESS STEEL INLET THREAD

MEMBRANE FIXED BUTYL RUBBER MEMBRANE REPLACEABLE TYPE

FLANGE STAINLESS STEEL MAX PRESSURE 10 BAR/ 150 PSI

PRE-CHARGE PRESSURE 1.5 BAR

WORKING TEMPRATURE 20 DEGREE C/+99 DEGREE C

FEATURES

NO MAINTENANCE
LEAK FREE, ORING SEALED, AIR VALVE CAP
COMPREHENSIVE TESTING
SINGLE DIAPHARM DESIGN
3MM THICKNESS STAINLESS STEEL WATER CONNECTION
PATENTED STAINLESS STEEL WATER CONNECTION
REPLACEABLE MEMBRANE
BUTYL DIAPHARM













BTALI®

PRESSURE TANK BT 80 LVPT

VOLTAGE / FREQUENCY

220V/50HZ

Specifications

CÖNNECTOR 1" STAINLESS STEEL INLET THREAD

MEMBRANE FIXED BUTYL RUBBER MEMBRANE REPLACEABLE TYPE

FLANGE STAINLESS STEEL MAX PRESSURE 10 BAR/ 150 PSI

PRE-CHARGE PRESSURE 1.5 BAR

WORKING TEMPERATURE 20 DEGREE C/+99 DEGREE C

FEATURES

NO MAINTENANCE
LEAK FREE, ORING SEALED, AIR VALVE CAP
COMPREHENSIVE TESTING
SINGLE DIAPHARM DESIGN
3MM THICKNESS STAINLESS STEEL WATER CONNECTION
PATENTED STAINLESS STEEL WATER CONNECTION
REPLACEABLE MEMBRANE
BUTYL DIAPHARM



EASY TRANSPORT











BTALI®

PRESSURE TANK BT 100 LVPT

VOLTAGE / FREQUENCY

220V/50HZ

Specifications

CONNECTOR 1" STAINLESS STEEL INLET THREAD

MEMBRANE FIXED BUTYL RUBBER MEMBRANE REPLACEABLE TYPE

FLANGE STAINLESS STEEL MAX PRESSURE 10 BAR/ 150 PSI

PRE-CHARGE PRESSURE 1.5 BAR

WORKING TEMPRATURE 20 DEGREE C/+99 DEGREE C

FEATURES

NO MAINTENANCE
LEAK FREE, ORING SEALED, AIR VALVE CAP
COMPREHENSIVE TESTING
SINGLE DIAPHARM DESIGN
3MM THICKNESS STAINLESS STEEL WATER CONNECTION
PATENTED STAINLESS STEEL WATER CONNECTION
REPLACEABLE MEMBRANE
BUTYL DIAPHARM



EASY Transport















374 LI INTERNATIONAL

Authorised Dealer / Distributor



- www.btaliinternational.com
 info@btaliinternational.com
- _btaliinternational_
- @btaliinternational8673